

Technical Data Sheet

Date of Issue 16/04/2021

Rev. 01_09/06/2021

9085

Contractor Premium Grade Duct Tape

**Product Description**

Professional grade, PE laminated synthetic cloth duct tape, coated with a specialized adhesive formulation resistant at low temperatures and able to adhere perfectly to multiple surfaces, especially rough surfaces as civil walls, concrete, tile, porfido and granite.

Characterized by an excellent holding power, traction resistance and hand tearability, it is suitable for high demand contractor applications like protection of windows frames, sills, facades and other surfaces during wall plastering and painting at construction sites.

For clean removal long-term UV exposure not recommended (max. 1 week).

Features

- Easy tear
- Low temperature resistance
- Easy to remove without residues at low temperatures
- Excellent conformability
- Suitable for rough surfaces
- Perfectly waterproof
- Excellent low-temperature bonding

Main Applications

- Protection of window frames and sills during plastering and painting
- Various application in construction and house building at low temperatures
- Splicing, repair and patching of PE sheeting

Technical Data

	Metric	Imperial Units	Test Method
Total weight*	180 g/m ²	180 g/m ²	ISO 536
Total thickness*	210 µm	8.3 mils	Internal
MD tensile strength*	43 N/cm	24.6Lbs/in	AFERA 5004/PSTC 131
MD elongation at break*	17 %	17 %	AFERA 5004/PSTC 131
Adhesion to steel plate*	8.0 N/cm	73.1 oz/in	AFERA 5001/PSTC 101
Service temperature	-15°C / 60°C	5°F / 140°F	

Backing material

PE laminated synthetic cloth

Type of adhesive

Synthetic rubber resin - solvent free

*Typical value

Available colour

White



Silver



Black



Orange



Yellow

Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. PPM Industries reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. PPM Industries does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.